



pro R Design: IP44.de

Lichttechnik:
230V Power LED
2700K + 3000K
L70/50.000 h

Reflektor: Flood
dimmbar

Installation:
2 x Kabeleinführung;
Anschlussklemme
3 x 1,5 mm²

Material:
Aluminiumguss
pulverbeschichtet
Sicherheitsglas klar

Schutzart:
IP65

Lichtrichtung:

light technology:
230V Power LED
2700K + 3000K
L70/50.000 h


reflector: flood
dimmbare

installation:
2 x cable entry point;
connection terminal
3 x 1,5 mm²

material:
aluminium die-casting
powder-coated
safety glass clear

protection class:
IP65

light direction:



Farbe colour	2700K		3000K	
	Art.-Nr. item no.	Systemleistung system perform.	Art.-Nr. item no.	Systemleistung system perform.
anthracite RAL 7016	91810-27- R-AN	15 W/1099 lm	91810-R-AN	15 W/1150 lm
space grey	91810-27- R-SG	15 W/1099 lm	91810-R-SG	15 W/1150 lm
pure white RAL 9016	91810-27- R-WH	15 W/1099 lm	91810-R-WH	15 W/1150 lm
deep black RAL 9005	91810-27- R-BL	15 W/1099 lm	91810-R-BL	15 W/1150 lm

Größe in mm
size in mm