Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	e or trade mark:	VS Manufaktur e.K.				
Supplier's addre	ess: -					
Model identifie	r: P80-1					
Type of light so	urce:					
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS		
Light source cap	o-type	СоВ				
(or other electri	ic interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:		Nein	Envelope:	-		
High luminance	High luminance light source: Nei					
Anti-glare shield	d:	Ja	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		20	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		2 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	18503100		
On-mode power (P _{on}), expressed in W		20,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,10		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	95		
Outer	Height	1 350	Spectral power	See image		
dimensions without	Width	80	distribution in the	in last page		
without	Depth	80				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,290			
		coordinates (x and y)	0,390			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	60	Survival factor	0,99			
the lumen maintenance factor	0,99					

(a)'-': not applicable; (b)'-': not applicable;